

### 3-Chip DLP™ Laser light source models

Lens not included with 3-Chip DLP™ models.



**PT-RQ50K** 50,000 lm Native 4K<sup>1</sup>  
51,000 lm (Center)



**PT-RQ45K** 42,000 lm\* 4K<sup>2</sup>  
43,600 lm\* (Center)

\*Brightness is tentative.



**PT-RQ35K2** 30,500 lm 4K<sup>2</sup>  
32,000 lm (Center)



**PT-RZ34K2** 30,500 lm WUXGA  
32,000 lm (Center)



**PT-RQ25K** 20,000 lm 4K<sup>2</sup>  
21,000 lm (Center)



**PT-RZ24K** 20,000 lm WUXGA  
21,000 lm (Center)



**PT-RQ18K** 16,000 lm 4K<sup>2</sup>  
16,800 lm (Center)



**PT-RZ17K** 16,000 lm WUXGA  
16,800 lm (Center)

### 1-Chip DLP™ Laser light source models

Lens not included with 'L' models.



**PT-HTQ20/L** 20,000 lm\* 4K<sup>2</sup>  
20,400 lm\* (Center)

\*Brightness is tentative.



**PT-REQ15/L** 15,000 lm 4K<sup>2</sup>  
15,500 lm (Center)



**PT-REQ12/L** 12,000 lm 4K<sup>2</sup>  
12,400 lm (Center)



**PT-REQ10/L** 10,000 lm 4K<sup>2</sup>  
10,300 lm (Center)



**PT-REQ80/L** 8,000 lm 4K<sup>2</sup>  
8,200 lm (Center)



**PT-REZ15/L** 15,000 lm WUXGA  
15,500 lm (Center)



**PT-REZ12/L** 12,000 lm WUXGA  
12,400 lm (Center)



**PT-REZ10/L** 10,000 lm WUXGA  
10,300 lm (Center)



**PT-REZ80/L** 8,000 lm WUXGA  
8,200 lm (Center)

### 1-Chip DLP™ Laser light source models

Lens not included with 'L' models.



**PT-RQ7L** 7,500 lm 4K<sup>6</sup>  
7,700 lm (Center)



**PT-RQ6L** 6,500 lm 4K<sup>6</sup>  
6,700 lm (Center)



**PT-RZ7L** 7,500 lm WUXGA  
7,700 lm (Center)



**PT-RZ6L** 6,500 lm WUXGA  
6,700 lm (Center)

### 1-Chip DLP™ Laser light source models (Lens fixed)



**PT-FRQ60** 6,000 lm 4K<sup>6</sup>  
6,200 lm (Center)



**PT-FRQ50** 5,200 lm 4K<sup>6</sup>  
5,400 lm (Center)



**PT-FRZ60** 6,000 lm WUXGA  
6,200 lm (Center)



**PT-FRZ50** 5,200 lm WUXGA  
5,400 lm (Center)



**PT-FRZ55** 5,000 lm WUXGA  
5,200 lm (Center)

### LCD Laser light source models

Lens not included with 'L' models.



**PT-MZ20KL** 20,000 lm WUXGA  
20,400 lm (Center)



**PT-MZ17KL** 16,500 lm WUXGA  
16,900 lm (Center)



**PT-MZ14KL** 14,000 lm WUXGA  
14,400 lm (Center)




**PT-MZ11KL** 11,000 lm WUXGA  
11,400 lm (Center)



**PT-MZ882** 8,200 lm WUXGA  
8,400 lm (Center)



**PT-MZ782** 7,500 lm WUXGA  
7,700 lm (Center)



**PT-MZ682** 6,500 lm WUXGA  
6,700 lm (Center)

### LCD Laser light source models (Lens fixed)



**PT-VMQ85** 8,000 lm 4K<sup>8</sup>  
8,200 lm (Center)



**PT-VMQ75** 7,300 lm 4K<sup>8</sup>  
7,500 lm (Center)



**PT-VMQ65** 6,500 lm 4K<sup>8</sup>  
6,700 lm (Center)



**PT-VMZ82** 8,000 lm WUXGA  
8,200 lm (Center)



**PT-VMZ72** 7,300 lm WUXGA  
7,500 lm (Center)



**PT-VMZ62** 6,500 lm WUXGA  
6,700 lm (Center)



**PT-VMZ51** 5,200 lm WUXGA  
5,400 lm (Center)



**PT-VMZ5ES** 5,200 lm WUXGA  
5,400 lm (Center)



**PT-LMZ460** 4,600 lm WUXGA  
4,800 lm (Center)



**PT-LMZ420** 4,200 lm WUXGA  
4,400 lm (Center)

### LCD Laser light source models (Lens fixed)



**PT-VMZ7ST** 7,000 lm WUXGA  
7,200 lm (Center)



**PT-VMZ6ST** 6,200 lm WUXGA  
6,400 lm (Center)



**PT-TMZ400** 4,000 lm WUXGA  
4,200 lm (Center)

### LCD Laser light source models (Lens fixed)



**PT-CMZ50** 5,200 lm WUXGA  
5,400 lm (Center)

### Media Processor



**ET-FMP50**  
**ET-FMP20**

**ET-SBFMP10** Function board type

- Resolution 4096 x 2160 Pixels.
- Resolution 3840 x 2400 Pixels (Quad Pixel Drive: ON).
- Only when the optional TY-SB01DL DIGITAL LINK Terminal Board is loaded.
- Available in Japan, US and Canada 5: Product availability varies by country or region.
- Resolution 3840 x 2160 Pixels (Quad Pixel Drive: ON).
- HDMI/DIGITAL LINK input only.
- Resolution 3840 x 2400 Pixels (achieved with 2-axis pixel-shifting technology)
- HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p.
- To operate wireless projection, the optional Wireless Module AJ-WM50 is required.
- HDMI input only. Supports signals up to 4K/30p.
- Available in black/white cabinet.
- The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing.

Note: [L] Lens-less model. The specifications are subject to change without notice. Regarding light output, measurement, measuring conditions, and the method of notation all comply with ISO/IEC 21118:2020 international standards. The results of brightness measurements that comply with ISO/IEC 21118:2020 and ANSI will be the same. Regarding center lumens, luminance is measured at the center of the screen.



For more information, please visit the website >>