

## SOLID SHINE Series



3-Chip DLP™ Laser light source models  
Lens not included with 3-Chip DLP™ models.

	<b>PT-RQ50K</b>	50,000 lm 51,000 lm (Center)	Native 4K <sup>1</sup>		
	<b>PT-RQ35K</b>	30,500 lm 32,000 lm (Center)	4K <sup>2</sup>		
	<b>PT-RZ34K</b>	30,500 lm 32,000 lm (Center)	WUXGA		
	<b>PT-RQ25K</b>	20,000 lm 21,000 lm (Center)	4K <sup>2</sup>		
	<b>PT-RZ24K</b>	20,000 lm 21,000 lm (Center)	WUXGA		
	<b>PT-RQ18K</b>	16,000 lm 16,800 lm (Center)	4K <sup>2</sup>		
	<b>PT-RZ17K</b>	16,000 lm 16,800 lm (Center)	WUXGA		
	<b>NEW PT-RZ14K<sup>3</sup></b>	14,000 lm 14,700 lm (Center)	WUXGA		



1-Chip DLP™ Laser light source models  
Lens not included with 'L' models.

	<b>PT-REQ15/L</b>	15,000 lm	4K <sup>2</sup>		
	<b>PT-REQ12/L</b>	12,000 lm 12,400 lm (Center)	4K <sup>2</sup>		
	<b>PT-REQ10/L</b>	10,000 lm 10,300 lm (Center)	4K <sup>2</sup>		
	<b>PT-REQ80/L</b>	8,000 lm 8,200 lm (Center)	4K <sup>2</sup>		
	<b>Preliminary PT-REZ15/L</b>	15,000 lm	WUXGA		
	<b>NEW PT-REZ12/L</b>	12,000 lm 12,400 lm (Center)	WUXGA		
	<b>PT-REZ10/L</b>	10,000 lm 10,300 lm (Center)	WUXGA		
	<b>PT-REZ80/L</b>	8,000 lm 8,200 lm (Center)	WUXGA		



1-Chip DLP™ Laser light source models  
Lens not included with 'L' models.

	<b>PT-RQ7L</b>	7,500 lm	4K <sup>5</sup>		
	<b>PT-RQ6L</b>	6,500 lm	4K <sup>5</sup>		
	<b>PT-RZ7L*</b>	7,500 lm	WUXGA		
	<b>PT-RZ6L*</b>	6,500 lm	WUXGA		
	<b>PT-RZ790/L</b>	7,000 lm 7,200 lm (Center)	WUXGA		
	<b>PT-RZ690/L</b>	6,000 lm 6,200 lm (Center)	WUXGA		



1-Chip DLP™ Laser light source models (Lens fixed)

	<b>PT-FRQ60</b>	6,000 lm 6,200 lm (Center)	4K <sup>7</sup>		
	<b>PT-FRQ50</b>	5,200 lm 5,400 lm (Center)	4K <sup>7</sup>		
	<b>PT-FRZ60</b>	6,000 lm 6,200 lm (Center)	WUXGA		
	<b>PT-FRZ50</b>	5,200 lm 5,400 lm (Center)	WUXGA		
	<b>Short Throw model PT-FRZ55*</b>	5,000 lm 5,200 lm (Center)	WUXGA		



LCD Laser light source models

	<b>PT-MZ20KL</b>	20,000 lm	WUXGA		
	<b>PT-MZ17KL</b>	16,500 lm	WUXGA		
	<b>PT-MZ14KL</b>	14,000 lm	WUXGA		
	<b>PT-MZ11KL</b>	11,000 lm	WUXGA		
	<b>Preliminary PT-MZ882</b>	8,200 lm	WUXGA		
	<b>PT-MZ782</b>	7,500 lm	WUXGA		
	<b>PT-MZ682</b>	6,500 lm	WUXGA		
	<b>PT-MZ880</b>	8,000 lm	WUXGA		
	<b>PT-MZ780</b>	7,000 lm	WUXGA		
	<b>PT-MZ680</b>	6,000 lm	WUXGA		



LCD Laser light source models (Lens fixed)

	<b>PT-VMZ71*</b>	7,000 lm	WUXGA		
	<b>PT-VMZ61*</b>	6,200 lm	WUXGA		
	<b>PT-VMZ51</b>	5,200 lm	WUXGA		
	<b>PT-VMZ51S</b>	5,200 lm	WUXGA		
	<b>PT-VMZ41</b>	4,500 lm	WUXGA		
	<b>PT-VMW61</b>	6,200 lm	WXGA		
	<b>PT-VMW51</b>	5,200 lm	WXGA		
	<b>PT-LMZ460</b>	4,600 lm	WUXGA		
	<b>PT-LMZ420</b>	4,200 lm	WUXGA		
	<b>PT-LMW460</b>	4,600 lm	WXGA		
	<b>PT-LMW420</b>	4,200 lm	WXGA		
	<b>PT-LMX460</b>	4,600 lm	XGA		
	<b>PT-LMX420</b>	4,200 lm	XGA		






LCD Laser light source models (Lens fixed)

	<b>PT-TMZ400</b>	4,000 lm	WUXGA		
	<b>PT-TMW380</b>	3,800 lm	WXGA		
	<b>PT-TMX380</b>	3,800 lm	XGA		



LCD Laser light source models (Lens fixed)

	<b>PT-CMZ50</b>	5,200 lm	WUXGA		
--	-----------------	----------	-------	--	--



	<b>PT-VW360</b>	4,000 lm	WXGA		
	<b>PT-VX430</b>	4,500 lm	XGA		
	<b>PT-LW376</b>	3,600 lm	WXGA		
	<b>PT-LW336</b>	3,100 lm	WXGA		
	<b>PT-LB426</b>	4,100 lm	XGA		
	<b>PT-LB386</b>	3,800 lm	XGA		
	<b>PT-LB356</b>	3,300 lm	XGA		
	<b>PT-LB306*</b>	3,100 lm	XGA		
	<b>PT-TW381R</b>	3,300 lm	WXGA		
	<b>PT-TW380</b>	3,300 lm	WXGA		
	<b>PT-TX440*</b>	3,800 lm	XGA		
	<b>PT-TX350*</b>	3,200 lm	XGA		

	<b>ET-FMP50</b>				
	<b>ET-FMP20</b>				
	<b>ET-SBFMP10</b>				SDM type

1: Resolution 4096 x 2160 Pixels. 2: Resolution 3840 x 2400 Pixels (Quad Pixel Drive: ON). 3: Available in Japan, US and Canada. 4: The availability varies depending on the country. 5: With Smooth Pixel Drive ON. 6: HDMI/DIGITAL LINK input only. 7: Resolution 3840 x 2160 Pixels (With Quad Pixel Drive). 8: HDMI input only. Supports signals up to 4K/30p. 9: HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p. 10: To operate wireless projection, the optional Wireless Module AJ-WM50 is required. 11: To operate wireless projection, the optional Wireless Module ET-WML100 (Stock limited)/AJ-WM50 is required.

\*: Available in black/white cabinet. : The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing. Note: [L] Lens-less model. The specifications are subject to change without notice. For more information, please visit the website >> [panasonic.net/cns/projector/](http://panasonic.net/cns/projector/)